

GRUPPI ELETTROGENI PER ATTACCO AL TRATTORE

Questi gruppi elettrogeni compatti e facili da usare, sono completi di base con attacco a 3 punti per un facile fissaggio su qualsiasi trattore.

La trasmissione avviene tramite un giunto cardanico (escluso dalla nostra fornitura) applicato tra la presa di forza del trattore e il moltiplicatore del gruppo.

Il quadro di comando manuale fissato sul gruppo è completo della seguente strumentazione: Interruttore magnetotermico differenziale di protezione, voltmetro, 2 prese a norme CEE.

A richiesta: amperometro, frequenzimetro, carrello per traino lento, Regolatore Elettronico, versione in IP44.

GENERATING SET FOR TRACTOR COUPLING

These generating sets are supplied completed with a 3 points base for an easy coupling with every type of tractor.

The power is transmitted through a cardan joint (not included in our supply) between the power take-off and the overgear mounted on the generator.

The manual panel is fixed on the generating set completed with the following instruments: automatic circuit breaker, voltmeter, 2 sockets an accordance with EEC regulation or terminal box.

Upon request: ammeter, frequencymeter, wheels, Electronic Regulator, version with protection IP44.

SERIE TR
3000 GIRI/MIN - 3000 R.p.m. - 3000 TR/MN

MODELLO MODEL	CONTINUI CONTINUOUS		EMERGENZA STAND-BY		GIRI ENTRATA R.P.M. ENTRY	GIRI ALTERNATORE R.P.M. GENERATOR	HP TRATTORE HP TRACTOR	PESO WEIGHT	Dimensioni (mm) Dimensions (mm)		
	KVA	KW	KVA	KW					L	LW	H
CGM 6 TR	6	5	6,6	5,5	440	3000	20	80	820	900	800
CGM 8 TR	8	6,4	8,8	7	440	3000	20	90	800	900	850
CGM 10 TR	10	8	11	8,8	440	3000	20	100	800	900	850
CGM 12.5 TR	12,5	10	13,8	11	440	3000	30	105	820	900	800
CGM 15 TR	15	12	16,5	13,2	440	3000	30	125	800	900	850
CGM 20 TR	20	16	22	17,6	440	3000	45	140	800	900	850
CGM 25 TR	25	20	27,5	22	440	3000	45	215	920	950	900
CGM 30 TR	30	24	33	26,4	440	3000	60	250	920	950	900
CGM 40 TR	40	32	44	35,2	440	3000	75	270	920	950	900

1500 GIRI/MIN - 1500 R.p.m. - 1500 TR/MN

CGM 10 TRL	10	8	11	8,8	430	1500	20	135	800	900	850
CGM 15 TRL	15	12	16,5	13,2	430	1500	30	150	800	900	850
CGM 20 TRL	20	16	22	17,6	430	1500	45	200	920	950	900
CGM 25 TRL	25	20	27,5	22	430	1500	45	230	920	950	900
CGM 30 TRL	30	24	33	26,4	430	1500	60	260	920	950	900
CGM 42 TRL	42	33,6	46,2	37	430	1500	80	390	1150	1270	1000
CGM 50 TRL	50	40	55	44	400	1500	100	408	1100	1270	1100
CGM 63 TRL	63	50,4	69,3	55,5	430	1500	120	430	1150	1270	1000
CGM 70 TRL	70	56	77	61,6	400	1500	120	450	1100	970	1100
CGM 75 TRL	75	60	87	82,5	400	1500	140	540	1100	1270	1100