

# PUMP OVER FERMENTING TANKS

Artikel	Grapeskins content (ca.70%)	Content Lt	D mm	H mm	Z mm	P mm	F mm
UTx344	1.350	1.800	1274	1500	2200	800	500
UTx345	1.600	2.100	1370	1500	2200	800	500
UTx346	1.700	2.300	1433	1500	2200	800	500
UTx347	1.800	2.400	1274	2000	2700	950	500
UTx348	2.200	2.900	1370	2000	2700	950	500
UTx330	2.200	3.000	1592	1500	2280	800	500
UTx349	2.300	3.100	1433	2000	2700	950	500
UTx331	2.600	3.500	1592	1750	2530	800	500
UTx332	3.000	4.000	1592	2000	2780	950	500
UTx340	3.600	4.800	1592	2500	3300	950	500
UTx333	3.600	4.800	1751	2000	2800	950	500
UTx334	4.500	6.000	1751	2500	3300	950	500
UTx335	5.000	6.800	2070	2000	2850	950	500
UTx341	5.400	7.200	1751	3000	3800	950	500
UTx336	5.700	7.600	2070	2250	3100	950	500
UTx337	6.300	8.400	2070	2500	3350	950	500
UTx338	7.300	9.700	2229	2500	3380	950	500
UTx342	7.350	9.800	2070	3000	3850	950	500
UTx339	8.800	11.700	2229	3000	3880	950	500
UTx343	9.750	13.000	2388	3000	3880	950	500
UTx350	13.000	17.300	2229	4500	5380	950	500
UTx351	14.800	19.800	2388	4500	5380	950	500

**Material:** W.Nr. 1.4301 BA (AISI 304 – V2A)

**Cover:** W.Nr. 1.4401 2B (AISI 316 – V4A)

**Surface:** outside marble finish and inside lild polished

**Standard equipment:**

3 regulated legs 500mm, 4 regulated legs 500mm from D1751

Flat bottom inclined 10%

Drain port: Ball valve 2" - 2"

Racking port: Ball valve 5/4"-5/4"

Sampling valve DN20

Digital thermometer with tube 1/2"

Level gauge DN20

Top Manway D400mm with pressure relief valve DN50

Ladder and crane hook

Rectangular manwaydoor (555x432mm)

Additional port: Ball valve 5/4"-5/4"

Deassembling filter on additional port

Decant tube DN40 with Ball valve 5/4"-5/4"

Deassembling rotational hat for sprinkling DN40

Cooling jacket (30% of jacket) with connections 3/4"

**Option:**

Oval manway Jaklič - welded frame 440x310mm

Double bottom with 1 or 2 heaters with thermostat

Temperature controller with motorised ball valve and adapter

