

STORAGE TANKS

Article Nr.	Content Lt	D mm	H mm	Z mm	M mm	P mm	L mm	F mm
WEx802	520	796	1000	1415	150	560	120	315
WEx803	650	796	1250	1665	150	650	120	315
WEx804	760	796	1500	1915	150	800	120	315
WEx824	520	925	750	1185	150	560	120	315
WEx821	650	925	900	1335	150	650	120	315
WEx827	700	925	1000	1435	150	650	120	315
WEx805	760	925	1100	1535	150	650	120	315
WEx825	850	925	1250	1685	150	650	120	315
WEx806	1.000	925	1500	1975	250	800	180	350
WEx828	1.000	796	2000	2450	250	800	180	350
WEx807	1.500	955	2000	2450	320	950	250	350
WEx808	1.500	1115	1500	2025	250	800	180	350
WEx809	2.000	1274	1500	2050	250	800	180	350
WEx822	2.000	1115	2000	2525	320	950	250	350
WEx829	2.300	1370	1500	2050	320	950	180	350
WEx810	2.600	1274	2000	2550	320	950	250	350
WEx811	3.000	1370	2000	2575	320	950	250	350
WEx830	3.100	1592	1500	2100	320	950	180	350
WEx820	3.200	1274	2500	3100	320	950	250	400
WEx831	3.700	1370	2500	3100	320	950	250	400
WEx812	4.000	1592	2000	2600	320	950	250	400
WEx832	4.500	1370	3000	3600	320	950	250	400
WEx813	5.000	1592	2500	3100	320	950	250	400
WEx826	5.500	1847	2000	2600	320	950	250	400
WEx814	6.000	1592	3000	3600	320	950	250	400
WEx833	6.900	1847	2500	3100	320	950	250	400
WEx815	7.100	1720	3000	3600	320	950	250	400
WEx816	8.200	1847	3000	3680	320	950	250	400
WEx834	8.600	2070	2500	3100	320	950	250	400
WEx835	10.000	2229	2500	3100	320	950	250	400
WEx817	10.300	2070	3000	3600	320	950	250	400
WEx836	11.900	2229	3000	3600	320	950	250	400
WEx837	12.100	2450	2500	3100	320	950	250	400
WEx838	12.200	1847	4500	5100	320	950	250	400
WEx818	12.500	1974	4000	4600	320	950	250	400
WEx839	14.400	2450	3000	3600	320	950	250	400
WEx840	15.300	2070	4500	5100	320	950	250	400
WEx819	15.800	2229	4000	4600	320	950	250	400
WEx841	17.800	2229	4500	5100	320	950	250	400
WEx842	18.000	2388	4000	4600	320	950	250	400
WEx823	20.500	2388	4500	5100	320	950	250	400
WEx843	21.500	2450	4500	5100	320	950	250	400

Material: W.Nr. 1.4301 BA (AISI 304 – V2A)

Cover: W.Nr. 1.4401 2B (AISI 316 – V4A) IIIc

Surface: outside marble finish and inside IIIc polished

Standard equipment:

3 legs (4 legs from D1720mm)

Drain port connection 5/4" with ball valve 5/4"-5/4" and cap

Racking port connection 5/4" with ball valve 5/4"-5/4" and cap

Sampling valve DN20

Connection 1/2" with cap

Level gauge DN20

Top inlet DN50 with pressure relief valve

Oval manway Jaklič - pressed frame

440x320mm (D925-D1370mm)

Oval manway Jaklič - welded frame

440x310mm (from D1592mm)

Oval manwaydoor 440x320mm inwards

opening (D796mm - vertical welded)

Ladder hook (from 1.000lt)

Crane hooks (from 2.000lt)

